## **ALASKA DIVISION OF GEOLOGICAL & GEOPHYSICAL SURVEYS GEOPHYSICAL REPORT 2014-1-5D** 2.577 2.234 1.994 1.808 1.656 1.526 1.414 1.319 1.234 1.157 0.910 0.858 0.811 0.766 0.724 0.684 0.610 0.576 0.544 0.513 0.458 0.408 0.345 0.292 0.277 0.263 0.249 0.236 0.224 0.212 0.200 0.190 · R 5 E R 6 E · · 146°50' 146°40' 146°30' 146°20' Section outlines from U.S. Geological Survey Mt Hayes A-5, 1949; A-6, 1950; B-5, 1956; B-6, 1956; Quadrangles, Alaska LOCATION INDEX FOR 1:63,360-SCALE MAPS **ANALYTIC SIGNAL** WITH DATA CONTOURS, WRANGELLIA SURVEY AREA, **SOUTH-CENTRAL ALASKA** APPROXIMATE MEAN DECLINATION, 2010 PARTS OF THE TALKEETNA MTNS, HEALY, AND MT HAYES QUADRANGLES by Laurel E. Burns, CGG, and Fugro GeoServices, Inc. 2014 DESCRIPTIVE NOTES SURVEY HISTORY The geophysical data were acquired with a DIGHEMV Electromagnetic (EM) system and a Fugro D1344 cesium magnetometer with a Scintrex CS3 cesium sensor. The EM and magnetic sensors were flown at a height of 100 feet. In addition the survey recorded data from radar and laser altimeters, GPS navigation system, 50/60 Hz monitors and video camera. Flights were performed with an AS-350-B3 Squirrel helicopter at a mean terrain clearance of 200 feet with a spacing primarily of a quarter of a mile, and one eighth of a mile for about 97.9 sq miles. Tie lines were flown perpendicular to the flight lines at intervals of approximately 3 miles. This map has been compiled and drawn under contract between the State of Alaska, Department of Natural Resources, Division of Geological & Geophysical Surveys Resources, Division of Geological & Geophysical Surveys (DGGS), and Fugro GeoServices, Inc. Airborne geophysical data for the area were acquired and processed by CGG in 2013 and 2014. Previously flown DGGS surveys adjacent to the current survey are shown in the location map by dashed lines, survey name, and date of publication. The project was funded by the Alaska State Legislature as part of the Alaska Strategic and Critical Minerals Assessment project, which is part of the Minerals Assessment project, which is part of the Alaska Airborne Geophysical and Geological Mineral Inventory Program. Millrock Exploration Corporation contributed infill data for a portion of the area shown above as denser hatching. A Novatel OEM5—G2L Global Positioning System was used for navigation. The helicopter position was derived every 0.5 seconds using post—flight differential positioning to a relative accuracy of better than 5 m. Flight path positions were projected onto the Clarke 1866 (UTM zone 6) spheroid, 1927 North American datum using a central meridian (CM) of 147°, a north constant of 0 and an east constant of 500,000. Positional accuracy of the presented data is better than ANALYTIC SIGNAL ANALYTIC SIGNAL CONTOURS Analytic signal is the total amplitude of all directions of magnetic gradient calculated from the sum of the squares of the three orthogonal gradients. Mapped highs \_\_\_\_ ..... 2.50 nT/metre All data and maps produced to date from this survey are available in digital format on DVD for a nominal fee through DGGS, 3354 College Road, Fairbanks, Alaska, 99709—3707, and are downloadable for free from the DGGS website (www.dggs.alaska.gov/pubs). Maps are also available on paper through the DGGS office, and are viewable online at the website in Adobe Acrobat .PDF file format \_\_\_\_ .... 0.50 nT/metre in the calculated analytic signal of magnetic parameter locate the anomalous source body edges and corners (e.g., contacts, fault/shear zones, etc.). Analytic signal maxima are located directly over faults and contacts, regardless of structural dip, and independently of the \_\_\_\_\_ .... 0.10 nT/metre accuracy of the presented data is better than 10 m with respect to the UTM grid. direction of the induced and/or remanent magnetizations. \_\_\_\_\_ \_\_\_ \_\_\_ \_\_\_ ..... 0.05 nT/metre file format.